

SECURITY KIT

1080P LITE 4 CH DVR with 2 Dome 2MPX ALL IN ONE Cameras

TECHNICAL SPECIFICATIONS FOR THE CAMERA	
Image Sensor	1/2.7" CMOS/1080P
Camera Resolution	2 Megapixel
Effective Pixels	1920(H) x 1080(V)
Infrared LED	24 pcs
Lens Mount	3,6mm
Format	AHD/CVI/TVI/CBVS
Operation Mode	UTC
Video Output	1CH BNC
Field of View	70° Degrees
Minimum Illumination	0 LUX (IR on)
IR Cut Filter	Yes
Night Vision Distance	82ft / 25m
Shutter Speed	(1/60 sec-1/100,000 sec)
Operative Temperature	14° ~ 122°F/ - 10° ~ 50°C
Ingress Protection	IP66
Power Supply	DC 12V/320mA (IR on)



MODEL: LX422DNHR-L

SPECIFICATIONS	
Video/Audio input	
Video compression	H.264
Analog video input	4-ch
HDTV input	Support HDTV input: 1080p25, 1080p30, 720p25, 720p30
AHD input	1080p25, 1080p30, 720p25, 720p30
HDCVI input	1080p25, 1080p30, 720p25, 720p30
CVBS input	Support
IP video input	Up to 4CH (960p resolution)
Audio input	1-ch RCA(Linear, 1kΩ)
Video/Audio output	
CVBS output	Support
HDMI/VGA output	1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz
Encoding resolution	Lite mode not enabled: 720p/VGA/WD1/4CIF/CIF;
Frame rate	Lite mode enabled: 1080p lite/720p lite/VGA/WD1/4CIF/CIF 1/16 fps ~ Real time frame rate
Video bit rate	32 Kbps ~ 4 Mbps
Audio output	1-ch RCA(Linear, 1kΩ)
Audio bit rate	64kbps
Dual stream	Support
Stream type	Video/Video&Audio
Synchronous playback	4-ch
Network management	
Remote connections	128
Network protocols	TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS
Hard disk	
SATA	1 SATA Interface
Capacity	Up to 6 TB capacity for each disk
External interface	
Two-way audio input	N/A
Network interface	1; 10M / 100M self-adaptive Ethernet interface
USB interface	2 USB 2.0 Interfaces
Serial interface	N/A
Alarm in/out	N/A
Power Consumption	12V DC // 1,7 Amp (without HDD)

