

SECURITY KIT

1080P LITE 8 CH DVR with 8 Bullet 2MPX ALL IN ONE Cameras



TECHNICAL SPECIFICATIONS FOR THE CAMERA	
Image Sensor	1/2.7" CMOS/1080P
Camera Resolution	2 Megapixel
Effective Pixels	1920(H) x 1080(V)
Infrared LED	18 SMD pcs
Lens Mount	3,6mm
Format	AHD/CVI/TVI/CBVS
Operation Mode	UTC
Video Output	1CH BNC
Field of View	94° Degrees
Minimum Illumination	0 LUX (IR on)
IR Cut Filter	Yes
Night Vision Distance	98ft / 30m
Shutter Speed	(1/30 sec-1/50,000 sec)
Operative Temperature	14° ~ 122°F/ - 10° ~ 50°C
Ingress Protection	IP66
Power Supply	DC 12V/320mA (IR on)

MODEL: LX882BNHR-L

SPECIFICATIONS	
Video/Audio input	
Video compression	H.264+/H.264
Analog video input	8-ch
HDTVI input	1080p25, 1080p30, 720p25, 720p30
AHD input	1080p25, 1080p30, 720p25, 720p30
HDCVI input	1080p25, 1080p30, 720p25, 720p30
CVBS input	Support
IP video input	Up to 8CH (960p resolution)
Audio input	1-ch RCA(Linear, 1k Ω)
Video/Audio output	
CVBS output	Support
HDMI/VGA output	1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz
Encoding resolution	Lite mode not enabled: 720p/VGA/WD1/4CIF/CIF; Lite mode enabled: 1080p lite/720p lite/VGA/WD1/4CIF/CIF
Frame rate	1/16 fps ~ Real time frame rate
Video bit rate	32 Kbps ~ 4 Mbps
Audio output	1-ch RCA(Linear, 1k Ω)
Audio bit rate	64kbps
Dual stream	Support
Stream type	Video/Video&Audio
Synchronous playback	16-ch
Network management	
Remote connections	128
Network protocols	TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS
Hard disk	
SATA	1 SATA Interface
Capacity	Up to 6 TB capacity for each disk
External interface	
Two-way audio input	N/A
Network interface	1; 10M / 100M self-adaptive Ethernet interface
USB interface	2 USB 2.0 Interfaces
Serial interface	N/A
Alarm in/out	N/A
Power Consumption	12V DC // 1,7 Amp (without HDD)

