

19" LCD Display Monitor

SPECIFICATIONS

L-M19LB1HIV-H

Display Type	LED Backlit TFT LCD
Screen Size	18.5"
Pixel Pitch (H x V)	0.30 mm x 0.30 mm
Maximum Resolution	1366 x 768
Brightness	200 cd/m ² (typical)
Contrast	600:1
Response Time	5 ms
Color	16.7 M
Viewing Angle	Horizontal 90°, vertical 65°

INPUT

VGA	VGA x 1
HDMI	HDMI x 1

MOUNTING

VESA	75 mm x 75 mm
------	---------------

GENERAL

Power Supply	100 to 240 VAC, 50/60 Hz
Consumption	< 25 W (on), < 0.5 W (standby)
Operating Temperature	32° F to 104° F (0° C to 40° C)
Operating Humidity	10% to 85% (no condensation)
Storage Temperature	- 4° F to 131° F (-20° C to 55° C)
Storage Humidity	5% to 95% (no condensation)
Dimensions (W x H x D)	17.54" x 10.83" x 1.76" (445.58 mm x 274.99 mm x 44.6 mm)
Weight	Gross weight: 7.72 lbs (3.5 kg), net weight: 9.17 lbs (2.8 kg)
Included Accessories	HDMI cable x 1, power cord x 1, base bracket x 1, user manual x 1, warranty card x 1

INTERFACE



Power Input



HDMI Digital Signal Output



VGA Analog Signal Input



MODEL: L-M19LB1HIV-H



HDMI-PORT



LED-Backlit



19"



VGA