

SECURITY KIT


1080P All in One 16 CH DVR with 8 Bullet 2MPX All in One Cameras

TECHNICAL SPECIFICATIONS FOR THE CAMERA

CAMERA	
Image Sensor	1/2,7" GC2033 CMOS/1080P
Camera Resolution	2 Megapixel
Effective Pixels	1920(H) x 1080(V)
Infrared LED	36 pcs
Lens Mount	3,6mm
Format	AHD/CVI/TVI/CBVS
Operation Mode	UTC
Video Output	1CH BNC
Field of View	70° Degrees
Minimum Illumination	0 LUX (IR on)
IR Cut Filter	Yes
Night Vision Distance	82ft / 25m
Shutter Speed	(1/60 sec-1/100,000 sec)
Operative Temperature	14° ~ 122°F/ - 10° ~ 50°C
Ingress Protection	IP66
Power Supply	DC 12V/320mA (IR on)



MODEL: LX682BN



1/2,7 CMOS



Motion Detection



Day and Night



Weatherproof



Notification Alarm



No Monthly Fees

TECHNICAL SPECIFICATIONS FOR DVR	
VIDEO	
Video Input	DVR: 16CH 1080P Hybrid: 12CH 1080P + 4CH IP 1080P / 8CH 1080P + 8CH IP 1080P / 4CH 1080P + 12CH IP 1080P NVR: 16CH IP 960P / 4CH 3MPX / 4CH 5MPX
Video Output	VGA, HDMI
Display Resolution	Up to 1080P (1920 x 1080)
Display Split	DVR: 1/4/8/9/16 Screen Hybrid: 1/4/8/9/16 Screen NVR: 1/4/8/9/16 Screen
AUDIO	
Audio Input	8 Channel RCA
Audio Output	1 Channel RCA
RECORDING	
Record Quality	Up to 1080P (1920 x 1080)
Video Compression	H.264 (High Profile)
Record Mode	Manual / Schedule / Motion / Alarms
PLAYBACK	
Simultaneously Playback	1/2/4 Channels
Backup Mode	USB Device, Web Browser, Mobile App
Playback Quality	Up to 1080P (1920 x 1080)
STORAGE	
HDD Port	2 SATA Port
HDD Capacity	Up to 8TB
EXTERNAL PORTS	
USB Port	2 Ports, USB 2.0
RS485	1 Port for PTZ Control
Ethernet	1 RJ-45 Port (10/100Mbps)
GENERAL	
Power Supply	DC 12V/3A
Video System	NTSC/PAL Switch Selectable
Remote Access	Cloud System For Remote Access, NO Port Mapping
Compatibility For	IOS, Android
Compatible Video Format	AHD/TVI/CVI/CBVS



LOGAN LIVE FREE APP

